

# TM RANGE



## PADLOC II

- 1-STEP KNOCK-IN/KNOCK-OUT PROCESS
- SIMPLE TOOTH REMOVAL
- SUPERIOR QUALITY



## WEARPART HOME

### SELECT TEETH TYPE & PILOT

The padloc advanced tooth locking system Ensures the tooth is locked in tight with a 1-step knock-in/knock-out process. Padlock teeth do not require the use of special tools to insert or remove and will fit most types of pockets - excluding d665TL Truloc pockets.

#### FIRST

CHOOSE THE DESIRED TOOTH CONFIGURATION TO SUIT GROUND CONDITIONS



### TOOTH CONFIGURATIONS


#### FLAT & CHISEL TEETH

Soft clay / General ground conditions. Outer flat teeth cut the correct diameter and protect the flights / pockets. Inner chisel teeth fracture and break up the ground.

OR

#### FLAT TEETH

Sticky clay and non-fracturable ground. Flat teeth 'slice' the clay for easier drilling and a cleaner finish.



GENERAL PURPOSE / FRACTURABLE & SOFT ROCK

- GENERAL PURPOSE
- MACHINES 5-24T



#### TM-3 OUTER

SUITS A6 / A8  
POCKET - TM-H

- GENERAL PURPOSE
- MACHINES 5-24T



#### TM-C-3 INNER

SUITS A6 / A8  
POCKET - TM-H

- GENERAL PURPOSE
- MACHINES 5-24T



#### PM-HX-3 PILOT

SUITS A6 / A8  
SOCKET - D627