



## Magnum Mulcher

The Digga Magnum Mulcher provides High Flow Skid Steer Loaders & Excavators up to 20 tonne with the versatility of grinding small and large material, trees or brush, even above ground stumps with just one operator. Debris can be mulched back into the soil for faster decomposition. Magnum is the perfect value adding attachment for clearing firebreaks, land clearing, maintenance of park or forestry trails, vegetation management and re-mediation.

### Features:

- Hydraulic driven, self aligning belt drive; low maintenance and great durability.
- Fixed hammers with replaceable carbide teeth.
- Shreds up to 8" diameter hardwood trees.
- Designed to operate at 2,000 RPM.
- Adjustable push bar.
- Optional oil cooler available in both field and/or factory installation.
- Replaceable abrasion resistant AR400 wear plate on skid shoes.
- On-board pressure gauge easily viewed from operators station to monitor system pressure (N/A MM60E models).
- Deflector door standard to control particle size and discharge direction (optional for MM60E).

### Machine suitability:

High Flow Skid Steer Loaders & Excavators up to 20T.

### Accessories:

Complete with hoses, couplers, multi-fit frame, Integrated Oil Cooler and pressure gauge.

Specifications	MM60S	MM60E
Width	1850mm	1850mm
Cutting Width	1520mm	1520mm
Number Teeth	44	44
Weight (kg)	1150kg	1230kg
Hydraulic Flow (LPM)	114-170	114-227

## 5 Reasons to Buy!

Reason 1 Adjustable Bent Axis Motor	Reason 2 Integrated Hydraulic Oil	Reason 3 Unique Drive Belt	Reason 4 Patented Tooth Design	Reason 5 Heavy Duty Rotor Design
Ability to adjust hydraulic motor flow to match the output of the host machine.	Increases Production by cooling hydraulic oil and virtually eliminate down time required to let machine cool down.	Unique Chevron design 200HP drive belt and sprockets eliminate slippage.	Patented reversible split tooth design channels cut material through the centre of the teeth providing relief and consistent cut material.	3/4 inch Drum wall thickness. Five reinforcing stabilizers reducing rotor flex, resulting in increased bearing life.
Increases production by reducing recovery time.	Protects the host machines hydraulic system from damage due to constant overheating.	Eliminates the need for Tensioning devices, reduces load on Bearings	Reduces drag on motor increasing production	Through shaft design adds to rigidity.
		Significantly reduces down time and maintenance costs	Reversible tooth allows for quick field replacement without downtime.	



**DIGGA Head Office**  
**Brisbane QLD**  
 4 Octal Street,  
 Yatala QLD 4207  
 Ph: (07) 3807 3330  
 Fax: (07) 3807 1499

**DIGGA NSW**  
 1 Gallipoli St, Smeaton  
 Grange, NSW, 2567  
 Ph: (02) 4647 1400  
 Fax: (02) 4647 1433

**DIGGA VIC**  
 21 - 25 Villas Road  
 Dandenong VIC, 3175  
 Ph: (03) 9706 6171  
 Fax: (03) 9706 6164

**DIGGA WEST**  
 6/15 Yampi Way,  
 Willeton, WA, 6155  
 Ph: (08) 9457 1544  
 Fax: (08) 9457 0748

**Email:** info@digga.com **Web:** www.digga.com



AUTHORISED  
DIGGA DEALER